

IMPACT-TILE

#1 selling rubber Gym Tiles

A1 Rubber recommends a thorough cleaning and maintenance program for Impact-Tile gymnasium flooring.

MAINTENANCE GUIDE

Maintenance Guide:

Post installation protection and maintenance of Impact-Tile gymnasium flooring should be specified by the designer/architect. Impact-Tile flooring in most cases does not come pre-finished, therefore the flooring after installation should not be subjected to dirt, dust, debris and potential damage from the surrounding construction activities.

A1 Rubber recommends that the specifier should determine which party will be responsible for the initial cleaning and application of the Protect-A-Gloss finish to the floor. To perform the initial cleaning, brush the surface with a stiff bristle broom and then vacuum and dust mop until it is totally clean. Allow to dry thoroughly.

It is required that all Impact-Tile floors be coated with two coats of Protect-A-Gloss floor finish which should be applied with a 10mm nap roller prior to use. Provide sufficient curing time between coats as well as after the final coat before allowing foot traffic (this should be at least 24 hours).

It is recommended that daily/regular cleaning should be performed by sweeping, dust mopping or vacuuming to remove all dust, dirt and debris. For heavy cleaning use a solventless heavy cleaning agent.

It is recommended that Impact-Tile flooring from time to time, when the look calls for it, be re-finished with Protect-A-Gloss floor finish following the standard Protect-A-Gloss application procedures.