

## IMPACT-TILE

**#1 selling rubber Gym Tiles**

### Product Overview

Standard Impact Tiles are manufactured in 1 metre x 1 metre size, 15mm thick, with top bevelled edges around the perimeter. The individual weight of each tile makes them perfect for loose laid installations thereby eliminating adhesive costs and significantly reducing labour. This makes good sense for the fitness centre owners who can treat the floor as an asset which is removable if relocation is required.

Impact Tiles are mass produced so a simple range of colours are available with custom colours available upon request. Standard colours are a black base with either 6% blue, red or cork coloured speckles or straight black. Other thicknesses, base colours and speckle combinations are available by special custom order.

### Specifications

Material:	Polymerically bound recycled rubber and 6% EPDM.
Density:	760kg/m <sup>3</sup>
Thickness:	15mm
Dimensions:	1metre X 1 metre, bevelled edges
Wet Pendulum:	Class X, slip resistance
Dry Pendulum:	Class F, slip resistance
Tensile Stength:	1.40 N/mm <sup>2</sup>
Shore A hardness:	40
Fire Rating:	3.1KW/m <sup>2</sup> Mean
Smoke Value:	100%

### Applications

They are extremely popular in Gymnasiums, roof tops, balconies, break out areas and most internal flooring applications.

**Disclaimer:** The above specifications are derived from periodic tests taken on actual product from the manufacturing process. The data shown above represents the average values and /or performance calculated from these tests. Some variances are possible due to the use of recycled raw materials and common manufacturing tolerances. All users of the product despite our application examples should test for suitability of purpose prior to application. All orders for this product are subject to our standard Terms and Conditions of Sale.